



Meudon BI Skate



QUINETTE GALLAY RENAISSANCE

DESCRIPTION | BACKREST | SEAT PAN | ARMREST | PEDESTAL | UPHOLSTERY | STANDARDS | OPTIONS | REFERENCES

Datasheet product n° 5277 revision A

Update : 25-02-19

DESCRIPTION

Chair mounted in rows on lateral pedestals, with automatic tipping-up seat and sharing

- Centre to centre: 55 cm to 60 cm
- Backrest height measured on that floor: 93 cm
- Depth in closed position: 55 cm

BACKREST

Width: 45 cm or 49 cm, depending on centre to centre.

Ergonomic form with good lumbar support.

Plywood curved structure, 13.5 mm thick with a screwed plastic case, to allow fitting on pedestal.

CMHR polyurethane foam, density 25 to 30 kg/m³ glued to the plywood structure.

SEAT PAN

Width: 41 cm, 44 cm depending on centre to centre.

CMHR polyurethane foam, density 50 to 55 kg/m³, moulded onto a metal support.

Seat tipping by means of torsion springs concealed in boxes, on either side of the seat and assembled on the pedestal.

ARMREST

Width: 9 cm

Wood inner structure on top of a steel box, 85 µ epoxy treated, metal facade. Steel base 5 cm high.

CMHR polyurethane foam. Density 55 to 65 kg/m³.

Writing tablet type SKATE, Lexan resin, black coloured, dimension 26x30 cm.

Maximum load supported by the tablet: 10 kg.

PEDESTAL

Quinette Gallay "Bilboquet" tipping system, allowing swift and tool-less removal of seat.

Lateral pedestals shared by two chairs supporting a cradle that receives the backrest and seat pan.

Two fastening floor anchors per pedestal and simple assembly of the pedestal by four screws.

No adjustment nor maintenance required.

Black satin finish paint RAL 9005 corrosion protection 400 hours salt fog.

Minimum radius 9 mm.

Floor fixings:

On concrete: 60 mm minimum on thickness, 2 plugs and bolts 8-50per foot.

On wood: 38 mm minimum on thickness 4 bolts 7-50 per foot.

UPHOLSTERY

For back and seat, fabric with 5mm CMHR foam backing, finished with netting 15g/m².

Seat cover is removable by mean of zip.

Removable stapled armrests and back covers.

STANDARDS

Fire :

- EN1021 - 1&2 / AM18 compliant
- DIN 4102: upon request.
- BS 7176 Medium Hazard.
- SNV 198 - 898
- BS 5852 Crib 5 (clause 12: upon request).
- CAL117 and others: upon request.



OPTIONS.

- Embroidered seat numbering on backrest or seat pan (font Roman block, 25 mm high), other fonts available upon request.
- Embroidered row markers (font Roman medium, 50 mm high) or aluminium plates (font Optima Medium, 25 mm Height).
- Decorative stitches.
- Back shell in 13.5 mm beech plywood finished with 2 layers of polyurethane varnish.
- Various wood veneers and stain available upon request.
- Varnished beech writing tablet, stain.
- Pedestals adapted to slope and counter slope (maximum 15% slope).
- Removable seats in groups of two or individually.
- Quick-release floor fastening.
- Metal parts: RAL colours upon request.
- End of row aisle lighting.